



双槽型



双槽型
BRDD

订购编号示例

1 代号 - 2 D - 3 dr - 4 R - 5 追加加工代码
 BRDD - 40 - 7 - 1.6
 BRDD - 28 - 10 - 2.1 - DS

1 代号	主要尺寸														
	2 D	3 dr 指定单位 1mm	4 R	D ₁	D ₂	D ₃	L	B	W	附件紧定螺 钉规格	M (粗牙)	适用圆皮 带直径			
BRDD	15	3~8	1.1	12	13	17	14	3	4	M3×3	M3	2			
	20	4~10		16	18	22									
	30	4~12		20	28	32									
	20	3~10	1.6	16	17	22	16	3	5	M3×3	M3	3			
	30	5~12		20	27	32									
	45	5~20		30	37	42									
	23	5~12	2.1	20	19	25	18	3	6	M3×3	M3	4			
	28				24	30									
	30				26	32									
	40				36	42									
	45	5~18	2.6	25	41	47	20	4	7	M4×3	M4	5			
	48	5~20		30	44	50									
	28	5~12		20	23	30							20	3	
	40	5~20	3.1	30	35	42	22	4	8	M4×3	M4	6			
	50	5~20			30	45							52		
	28	5~12			22	22							30	22	3
	38	5~20			32	40							24	4	8
	48		42	50											
	50		44	52											
	60		54	62											
	75	5~20	4.1	30	69	77	30	5	10	M5×4	M5	8			
	100				94	102									
	50				42	52									
	60				52	62									
100	5~20	5.1	34	92	102	34	5	12	M5×4	M5	10				
60				50	62										
100				90	102										
140				130	142										

5 追加加工类型	外径缩短
代号	DS
示例图	
详细信息	切割外圆减少外径尺寸 皮带半径 /R 适用 R 尺寸 DS 1.1 D+0.8 1.6 D+1.2 2.1 D+1.6 2.6 D+1.8 仅适用于 R=1.1 · 1.6 · 2.1 · 2.6 的产品 外圆切割的加工面可能不 进行表面处理
指定方法	指定方法 DS

代号	材质	表面处理	附件
BRDD	铝合金	本色阳极氧化	2 个紧定螺钉 (35CrMo 四氧化三铁保护膜)

皮带滑轮
情 况