



中载型



SCEMP
平行向



SCEMV
垂直向

订购编号示例

1 代号 - 2 D - 3 L - 4 材料代码
SCEMP - 5 - 20 - M01

1 代号	2 D	3 L	d	动态负载时		初拉力 (N)	刚度系数 (N/mm)
				工作行程 S (mm)	工作极限载荷 (N)		
SCEMP	2	10	0.3	3.8	3.53	0.69	0.75
		15		6.7			0.42
		20		9.6			0.30
		25		12.6			0.23
		30		15.6			0.18
	3	15	0.4	6	4.41	0.88	0.59
		20		9			0.39
		25		12			0.29
		30		15.6			0.23
	4	15	0.5	6.5	6.37	1.18	0.78
		20		10.2			0.49
		25		13.9			0.39
		30		17.5			0.29
		35		20.3			0.26
SCEMP SCEMV (括号内尺寸仅属 SCEMP)	5	40	0.6	24	8.53	1.57	0.22
		45		28.4			0.25
		50		32.2			0.22
		55		36.3			0.18
		60		40			0.15
	6	20	0.8	6.7	17.26	3.53	2.06
		25		9.3			1.47
		30		12.7			1.08
		35		15.6			0.88
		40		18.7			0.69
		45		20.6			0.68
		50		24.5			0.57
		55		28			0.50
		60		29.7			0.47
		65		33.3			0.40
	8	25	1	9.1	24.52	4.9	2.16
		30		12.5			1.57
		35		15.4			1.27
		40		19.2			0.98
		45		22.2			0.88
		50		25			0.78
		55		28.6			0.70
		60		33.3			0.60
		65		36.3			0.55
		70		40			0.50

1 代号	2 D	3 L	d	动态负载时		初拉力 (N)	刚度系数 (N/mm)
				工作行程 S (mm)	工作极限载荷 (N)		
SCEMP SCEMV (括号内尺寸仅属 SCEMP)	10	30	1.2	10.4	30.99	5.49	2.45
		35		13.7			1.86
		40		17.3			1.47
		45		20			1.27
		50		24.8			0.98
		55		28.2			0.88
		60		31.6			0.78
		65		34.2			0.76
		70		38.8			0.67
		75		43.3			0.60
		80		47.2			0.55
		(90)		52			0.49
	12	35	1.6	8.5	62.76	14.71	5.69
		40		11.8			4.12
		45		14.3			3.33
		50		16.8			2.84
		55		19.3			2.45
		60		22.3			2.16
		65		24.5			1.96
		70		27.2			1.77
		75		28.8			1.67
		80		32.7			1.47
		90		36.3			1.35
		100		41			1.20
SCEMP	14	40	1.8	10.2	74.53	16.67	5.69
		45		13.1			4.41
		50		16.4			3.53
		55		19.7			2.94
		60		21.1			2.75
		65		24.6			2.35
		70		27.6			2.06
		75		31.1			1.86
		80		32.8			1.77
		90		37.5			1.60
		100		42.8			1.40
		125		60			1.00
	16	45	2 (仅限 M01 材质) 2.1 (仅限 M02 材质)	11.7	86.3	19.61	5.69
		50		15.1			4.41
		55		17.4			3.82
		60		21.3			3.14
		65		23.4			2.84
		70		26.8			2.45
		75		29.6			2.26
		80		32.7			2.10
		90		37.8			1.77
		100		45.3			1.47
		125		56.7			1.20
		150		71.5			0.95
	18	50	2.3	12.5	115.72	27.46	7.06
		55		15			5.88
		60		17.3			5.10
		65		20			4.41
		70		22.5			3.92
		75		25			3.53
		80		29			3.04
		90		33.6			2.65
		100		39.1			2.26
		125		53			1.70
		150		64.2			1.40
	20	60	2.6	14.7	150.04	36.28	7.75
		70		20			5.69
		80		25.2			4.51
		90		30.8			3.73
		100		36.1			3.14
		125		48.3			2.35
		150		59.5			1.95
		175		72.5			1.60
	24	70	3.2	14.7	225.55	56.88	11.47
		80		20.7			8.14
		90		24.9			6.77
		100		29.7			5.69
		125		41			4.12
		150		50.6			3.40
		175		61.4			2.80
		200		74.7			2.30

△ 初拉力、刚度系数为参考值。载荷 (kgf) = 载荷 N × 0.101972

代号	类型	1 材料代码	材质
SCEMP SCEMV	中载型	M01	SWP-A/B
		M02	SUS304-SWPB