



无挡圈双轴承嵌入型 · L 尺寸指定型

■ 产品特点: 可以 1mm 为单位指定固定座长度 (L 尺寸)。


轴
承




BDELD F
圆型



BDELD K
方型



BDELD T
对边切割型



其余 1/3

订购编号示例

1 代号 - 2 轴承型号 - 3 L - 4 S - 5 材料代码
BDELD F - 6800-2Z - 20 - 10 - A

1 代号	2 轴承型号	3 L 指定单位 1mm	4 S 指定单位 1mm	d	D _{H7}	D _{19/7}	D _r 公差	H	d _h	T	B	D	K	A	W	F	d ₁	H ₁	d ₂	材料规格有无		
																				轴承: 铜 固定座: 45#	轴承: 铜 固定座: A2017	轴承: 不锈钢
BDELD F BDELD K BDELD T	623-2Z	20 ~ 40	5 ~ 28	3	10	14	-0.006 -0.024	33	7	7	4	24	27	24	16		6.5	3.1	3.5		-	-
	624-2Z	20 ~ 40	5 ~ 28	4	13	17		35	9		5	26	28	26	18						-	-
	605-2Z	20 ~ 40	5 ~ 27		14	18		38	10		5	28	30	28	20						-	-
	625-2Z	30 ~ 40	10 ~ 22	5	16	20		40	12		5	30	31	30	22						-	-
	606-2Z	20 ~ 40	5 ~ 27		17	21	-0.007 -0.028	41	13		6	31	32	31	23		8	4.1	4.5			-
	626-2Z	30 ~ 50	10 ~ 32	6	19	24		44	15		6	34	34	34	25							
	67/8-2Z	20 ~ 40	5 ~ 27		12	16	-0.006 -0.024	35	10		3.5	26	28	26	18		6.5	3.1	3.5			
	69/8-2Z	25 ~ 50	5 ~ 37	8	19	24		44	15		6	34	34	34	25							
	608-2Z	20 ~ 50	5 ~ 37		22	27		47	18		7	37	36	37	29							
	628-2Z	30 ~ 50	10 ~ 32		24	30	-0.007 -0.028	50	20		8	40	37	40	32							
	6700-2Z	20 ~ 40	5 ~ 27		15	19		40	12		4	30	31	30	22							
	6800-2Z	20 ~ 40	5 ~ 27		19	24		44	15	8	5	34	34	34	25							
	6900-2Z	20 ~ 60	5 ~ 47	10	22	27		47	19		6	37	36	37	29							
	6000-2Z	30 ~ 60	10 ~ 42		26	32	-0.009 -0.034	52	22		8	42	39	42	34							
	6200-2Z	40 ~ 60	15 ~ 37		30	36		56	24		9	46	42	46	38		8	4.1	4.5			
	6701-2Z	20 ~ 40	5 ~ 27		18	23	-0.007 -0.028	44	15		4	34	34	34	25							
	6801-2Z	25 ~ 50	5 ~ 37		21	26		47	17		5	37	36	37	29							
	6901-2Z	30 ~ 60	10 ~ 42	12	24	30		50	21		6	40	38	40	31							
	6001-2Z	30 ~ 60	10 ~ 42		28	34	-0.009 -0.034	54	24		8	44	40	44	36							
	6201-2Z	40 ~ 70	15 ~ 47		32	38		58	26		10	48	43	48	40							
	6702-2Z	25 ~ 60	10 ~ 42		21	26	-0.007 -0.028	47	18		4	37	36	37	29							
	6802-2Z	25 ~ 60	10 ~ 42		24	30		50	20		5	40	37	40	32							
	6902-2Z	30 ~ 70	10 ~ 50	15	28	35		59	25		7	47	45	47	37							
	6002-2Z	40 ~ 70	15 ~ 45		32	38		62	28		9	50	46	50	40		9.5	5.1	5.5			
	6202-2Z	40 ~ 70	15 ~ 45		35	42		66	29		11	54	49	54	44							
	6803-2Z	25 ~ 60	10 ~ 40		26	32		52	22	10	5	42	39	42	34		8	4.1	4.5			
	6903-2Z	40 ~ 70	15 ~ 45		30	36	-0.009 -0.034	60	27		7	48	46	48	38							
	6003-2Z	40 ~ 70	15 ~ 45	17	35	42		66	31		10	54	50	54	44		9.5	5.1	5.5			
	6203-2Z	50 ~ 70	20 ~ 40		40	48		72	34		12	60	54	60	50							
	6704-2Z	30 ~ 70	10 ~ 50		27	33		59	23		4	47	45	41	35	23	8	4.1	4.5			
	6804-2Z	35 ~ 70	10 ~ 50		32	38		62	28		7	50	46	44	40	24	9.5	5.1	5.5			
	6904-2Z	45 ~ 70	15 ~ 44	20	37	45		72	34		9	59	54	54	47	24						
	6004-2Z	55 ~ 80	20 ~ 47		42	50		77	36		12	64	59	56	54	32						
	6204-2Z	55 ~ 80	20 ~ 49		47	54	-0.010 -0.040	81	40	11	14	68	62	59	58	34	11	6.1	6.6			
	6805-2Z	35 ~ 70	15 ~ 44		37	45	-0.009 -0.034	72	34		7	59	54	54	47	24				-	-	-
	6905-2Z	35 ~ 70	15 ~ 44		42	50		77	36		9	64	59	55	54	32				-	-	-
	6005-2Z	55 ~ 80	20 ~ 47		47	54	-0.010 -0.040	88	41		12	72	67	63	58	36				-	-	-
	6205-2Z	55 ~ 80	20 ~ 47		52	60		94	45	13	15	78	72	68	64	39	14	8.1	9			
	6806-2Z	35 ~ 70	15 ~ 42		42	50	-0.009 -0.034	77	36	11	7	64	59	56	54	32	11	6.1	6.6		-	-
	6906-2Z	35 ~ 70	15 ~ 42		47	54		88	41		9	72	67	62	58	36				-	-	-
	6006-2Z	55 ~ 80	20 ~ 47		55	62	-0.010 -0.040	96	48	13	13	80	73	70	66	40	14	8.1	9		-	-
	6206-2Z	55 ~ 120	20 ~ 87		62	70		104	55		16	88	79	77	74	44				-	-	-

材料说明

代号	类型	5 材料代码	材质		表面处理
			轴承	固定座	固定座
BDELD F	圆型	A	钢	45#	四氧化三铁保护膜
		B		45#	无电解镀镍
		C		A2017	本色阳极氧化处理
		F	不锈钢	0Cr18Ni9	-
BDELD K BDELD T	方型 对边切割型	A	钢	45#	四氧化三铁保护膜
		B		45#	无电解镀镍
		C		A2017	本色阳极氧化处理