





带挡圈双轴承嵌入型・L 尺寸指定型

■ 产品特点: 可以 1mm 为单位指定固定座长度 (L 尺寸)。



其余 1/3

BRDELDF
圆型

BRDELDF
方型

BRDELDT
对边切割型

订购编号示例

1 代号 - 2 轴承型号 - 3 L - 4 S - 5 材料代码
BRDELDF - 6800-2Z - 20 - 10 - A

1 代号	2 轴承型号	3 L 指定单位 1mm	4 S 指定单位 1mm	d	D _{H7}	D _{1g7}	D ₁ 公差	H	d _n	T	L ₁	B	D	K	A	W	F	d ₁	H ₁	d ₂	材料规格有无		
																					轴承: 钢 固定座: 45#	轴承: 钢 固定座: A2017	轴承: 不锈钢
BRDELDF BRDELDF BRDELDT	623-2Z	20 ~ 40	5 ~ 28	3	10	14	-0.006 -0.024	33	7	7	2.65	4	24	27	24	16	-	6.5	3.1	3.5			-
	624-2Z	20 ~ 40	5 ~ 28	4	13	17		35	9		2.65	5	26	28	26	18							-
	605-2Z	20 ~ 40	5 ~ 27	5	14	18	-0.007 -0.028	38	10	8	2.65	5	28	30	28	20							-
	625-2Z	30 ~ 40	10 ~ 22		16	20		40	12		2.65	5	30	31	30	22							-
	606-2Z	20 ~ 40	5 ~ 27	6	17	21		41	13		2.65	6	31	32	31	23							-
	626-2Z	30 ~ 50	10 ~ 32		19	24		44	15		2.65	6	34	34	34	25							-
	69/8-2Z	25 ~ 50	5 ~ 37	8	19	24		44	15	8	2.65	6	34	34	34	25							-
	608-2Z	20 ~ 50	5 ~ 37		22	27		47	18		2.65	7	37	36	37	29							-
	628-2Z	30 ~ 50	10 ~ 32	10	24	30	-0.009 -0.034	50	20		2.85	8	40	37	40	32							-
	6800-2Z	20 ~ 40	5 ~ 27		19	24		44	15		2.65	5	34	34	34	25							-
	6900-2Z	25 ~ 60	5 ~ 47		22	27		47	19		2.65	6	37	36	37	29							-
	6000-2Z	30 ~ 60	10 ~ 42		26	32		52	22	12	2.85	8	42	39	42	34							-
	6200-2Z	40 ~ 60	15 ~ 37	12	30	36		56	24		2.85	9	46	42	46	38							-
	6801-2Z	25 ~ 50	5 ~ 37		21	26		47	17		2.85	5	37	36	37	29							-
	6901-2Z	30 ~ 60	10 ~ 42		24	30		50	21		2.85	6	40	38	40	31							-
	6001-2Z	30 ~ 60	10 ~ 42	20	28	34	-0.007 -0.028	54	24	10	2.85	8	44	40	44	36							-
	6201-2Z	40 ~ 70	15 ~ 47		32	38		58	26		2.85	10	48	43	48	40							-
	6802-2Z	25 ~ 60	10 ~ 42		24	30		50	20		2.85	5	40	37	40	32							-
	6902-2Z	30 ~ 70	10 ~ 50		28	35		59	25	17	2.85	7	47	45	47	37							-
	6002-2Z	40 ~ 70	15 ~ 45	15	32	38	-0.009 -0.034	62	28		2.85	9	50	46	50	40							-
	6202-2Z	40 ~ 70	15 ~ 45		35	42		66	29		3.75	11	54	49	54	44							-
	6903-2Z	40 ~ 70	15 ~ 45		30	36		60	27		2.85	7	48	46	48	38							-
	6003-2Z	40 ~ 70	15 ~ 45		35	42		66	31	11	3.75	10	54	50	54	44							-
	6203-2Z	50 ~ 70	20 ~ 40	20	40	48	-0.010 -0.040	72	34		3.95	12	60	54	60	50							-
	6804-2Z	35 ~ 70	10 ~ 50		32	38		62	28		3.75	7	50	46	44	40							-
	6904-2Z	45 ~ 70	15 ~ 44		37	45		72	34		3.75	9	59	54	54	47							-
	6004-2Z	55 ~ 80	20 ~ 49		42	50		77	36	13	3.95	12	64	59	56	54							-
	6204-2Z	55 ~ 80	20 ~ 49	25	47	54	-0.009 -0.034	81	40		3.95	14	68	62	59	58							-
	6805-2Z	35 ~ 70	15 ~ 44		37	45		72	34		3.75	7	59	54	54	47							-
	6905-2Z	35 ~ 70	15 ~ 44		42	50		77	36		3.95	9	64	59	55	54							-
	6005-2Z	55 ~ 80	20 ~ 47		47	54		88	41	11	3.95	12	72	67	63	58							-
	6205-2Z	55 ~ 80	20 ~ 47	30	52	60	-0.009 -0.034	94	45		4.2	15	78	72	68	64							-
	6806-2Z	35 ~ 70	15 ~ 42		42	50		77	36		3.95	7	64	59	56	54							-
	6906-2Z	35 ~ 70	15 ~ 42		47	54		88	41		3.95	9	72	67	62	58							-
	6006-2Z	55 ~ 80	20 ~ 47	30	55	62	-0.010 -0.040	96	48	13	4.2	13	80	73	70	66							-
	6206-2Z	55 ~ 120	20 ~ 87		62	70		104	55		4.2	16	88	79	77	74							-

■ 材料说明

代号	类型	5 材料代码	材质		表面处理	附件
			轴承	固定座	固定座	挡圈
BRDELDF	圆型	A	钢	45#	四氧化三铁保护膜	弹簧钢
		B		45#	无电解镀镍	0Cr18Ni9
		C		A2017	本色阳极氧化处理	0Cr18Ni9
		E		A2017	本色阳极氧化处理	0Cr18Ni9
BRDELDF	方型	B	钢	45#	无电解镀镍	0Cr18Ni9
BRDELDT	对边切割型	A		45#	四氧化三铁保护膜	弹簧钢
		B		45#	无电解镀镍	0Cr18Ni9
		E		A2017	本色阳极氧化处理	0Cr18Ni9