


下部紧凑型



产品特点: 下部安装。



安装孔 (6个)



安装孔 (4个)



SMUXL SMUS3M
SMUL SMUS5M
SMUH SMUS8M
SMUT5
SMUT10

下部紧凑型

订购编号示例

1 代号 - 2 宽度代号
SMUL - 050

1 代号	2 宽度代号	W	A	B	T	h	L	P	d	安装孔数
SMUXL	025	6.4	36	24	6	1.25	25	12	4.5	4
	031	7.9		25				14		
	037	9.5		26				16		
	050	12.7		30				20		
SMUL	050	12.7	66	32	8	1.9	50	20	5.5	4
	075	19.1		38				26		
	100	25.4		46				33		
	150	38.1		58				46		
SMUH	075	19.1	89	38	10	2.3	70	26	5.5	6
	100	25.4		46				33		
	150	38.1		58				45		
	200	50.8		70				58		
SMUT5	10	10	35	26	6	1.2	25	16	4.5	4
	15	15		32				21		
	20	20		38				26		
	25	25		43				31		
SMUT10	15	15	70	34	8	2.5	50	22	5.5	6
	20	20		40				27		
	25	25		44				32		
	30	30		50				37		
SMUS3M	6	6	21	20	4	1.14	15	11	3.4	4
	10	10		25				15		
	15	15		30				20		
SMUS5M	10	10	35	26	6	1.81	25	16	4.5	4
	15	15		32				21		
	25	25		42				31		
SMUS8M	15	15	56	34	8	2.85	40	22	5.5	4
	25	25		44				32		
	30	30		50				37		
	40	40		60				47		

▲ 齿形以橡胶同步带、聚氨酯同步带为标准
▲ 皮带宽度以同步带为标准
▲ S □ M型的金属件也可用于P □ M型同步带

代号	类型	材质	表面处理	附件
SMUXL SMUL SMUH SMUT5 SMUT10 SMUS3M SMUS5M SMUS8M	下部紧凑型型	铝合金	本色阳极氧化处理	内六角螺钉