


两端双轴承型

产品特点：轮两侧各有一个轴承。



STT5D
两端双轴承型

订购编号示例

1 代号

-

2 齿数

-

3 匹配同步带类型

STT5D-20-T5-10

1 代号	2 齿数	3 匹配同步带类型	主要尺寸								轴承尺寸		
			dr	Dr	Ds	Dfo	Dfi	A	W	Dh	轴承型号	D	B
STT5D	18	T5-10	6	28.65	27.80	32	22	11	16	13	69/6-2Z×2	15	5
		T5-15						17	22				
		T5-20	8					22	27	16.5	69/8-2Z×2	19	6
		T5-25											
	20	T5-10	8	31.83	31.00	35	24	11	16	16.5	69/8-2Z×2	19	6
		T5-15						17	22				
		T5-20						22	27				
		T5-25						27	32				
	22	T5-15	10	35.01	34.25	40	27	17	22	19.5	6900-2Z×2	22	6
		T5-20						22	27				
		T5-25						27	32				
	24	T5-10	10	38.20	37.40	42	30	11	16	19.5	6900-2Z×2	22	6
		T5-15						17	22				
		T5-20						23	6000-2Z×2	26	8		
		T5-25										22	27
	25	T5-15	10	39.79	39.00	43	32	17	22	23	6000-2Z×2	26	8
		T5-20						22	27				
		T5-25						27	32				
		28						T5-15	10				
	T5-20		22	27									
	T5-25		27	32									
	30	T5-15	12	47.75	46.95	51	39	17	22	25	6001-2Z×2	28	8
		T5-20						22	27				
		T5-25						27	32				

⚠ 轴承精度等级：0 级（压入前） ⚠ 轴承采用压入方式

代号	类型	材质			表面处理
		主体	挡片	轴承	
STT5D	两端双轴承型	铝合金	铝合金	钢	本色阳极氧化处理

同步带轮